

Program LEQ Professional v. 6-2014 dla Windows

Projekt:

C:\Users\Biuro\Desktop\Hałas\Wariant realizacyjny\W.realizacyjny.dat

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0.500

Temperatura otoczenia 10 [°C]

Źródła punktowe

Nr	X [m]	Y [m]	z [m]	Pma	Symbol
1	488.2	672.0	0.5	54.8	T1
2	486.0	682.7	0.5	54.8	T2
3	506.4	681.0	0.5	54.8	T3
4	501.7	691.6	0.5	54.8	T4
5	507.8	703.4	1.0	98.0	Ł
6	366.0	530.0	0.5	62.3	P
7	374.6	536.1	0.5	62.3	P
8	383.1	542.2	0.5	62.3	P
9	391.7	548.3	0.5	62.3	P
10	400.2	554.4	0.5	62.3	P
11	408.8	560.6	0.5	62.3	P
12	417.3	566.7	0.5	62.3	P
13	425.9	572.8	0.5	62.3	P
14	434.4	578.9	0.5	62.3	P
15	443.0	585.0	0.5	62.3	P
16	447.0	597.0	0.5	62.3	P
17	451.6	606.6	0.5	62.3	P
18	456.1	616.1	0.5	62.3	P
19	460.7	625.7	0.5	62.3	P
20	465.3	635.3	0.5	62.3	P
21	469.9	644.9	0.5	62.3	P
22	474.4	654.4	0.5	62.3	P
23	479.0	664.0	0.5	62.3	P
24	476.2	636.8	1.0	79.0	PK

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŃKÓW :

Nr	X1 [m]	Y1 [m]	X2 [m]	Y2 [m]	X3 [m]	Y3 [m]	X4 [m]	Y4 [m]	h0 [m]	h [m]
1	551.2	692.4	476.0	629.6	488.0	614.8	563.6	678.0	0.0	5.0

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr	Źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1 L wew	79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.2	L wew	79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.3	L wew	79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000

	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
sc.4	L wew	79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
dach	L wew	79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	34.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

ródno nr 1 : ELEMENTY O RÓNEJ IZOLACYJNOŒCI AKUSTYCZNEJ

ściana nr : 1

Lp	x	y	dx	dy	R_el	R_63	R_125	R_250	R_500	R1000	R2000	R4000	R8000
1	60.0	0.0	5.0	3.5	16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	45.0	0.0	5.0	3.5	16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
3	80.0	0.0	5.0	3.5	16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

ściana nr : 3

Lp	x	y	dx	dy	R_el	R_63	R_125	R_250	R_500	R1000	R2000	R4000	R8000
1	10.0	3.0	70.0	0.8	16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Ekrany akustyczne :

WSPÓRZĘDNE WIERZCHOŒKÓW :

Nr	X1 [m]	Y1 [m]	X2 [m]	Y2 [m]	X3 [m]	Y3 [m]	X4 [m]	Y4 [m]	h0 [m]	h [m]
1	318.0	660.0	325.2	648.8	346.0	662.0	339.6	673.2	0.0	4.0
2	335.6	628.8	341.2	618.4	358.0	628.0	352.4	638.4	0.0	3.5
3	336.4	597.2	342.0	600.8	348.8	590.0	342.8	586.0	0.0	3.0
4	373.2	572.4	378.0	564.4	393.6	575.6	388.4	582.8	0.0	3.0
5	422.8	517.2	429.2	505.2	437.6	509.6	430.8	521.6	0.0	3.0
6	432.8	480.4	436.0	473.6	448.8	482.0	444.8	488.4	0.0	3.0
7	452.8	485.6	458.4	490.0	462.4	484.0	456.0	479.6	0.0	2.5
8	492.8	542.4	500.0	548.8	522.0	522.0	515.2	516.0	0.0	4.0
9	521.6	578.4	526.0	573.2	507.2	559.6	504.0	564.0	0.0	4.5
10	506.4	557.6	514.4	548.0	534.0	564.0	527.2	573.2	0.0	5.0
11	536.0	600.0	547.2	609.6	551.2	605.6	540.0	594.8	0.0	3.0
12	564.4	623.2	576.8	633.6	580.4	628.8	567.2	618.8	0.0	3.0
13	552.0	598.4	571.6	614.8	619.2	557.2	598.8	540.8	0.0	6.0
14	551.2	538.8	569.2	554.8	573.6	551.2	554.4	535.6	0.0	3.5
15	528.8	499.6	532.4	503.6	535.2	500.4	531.2	496.4	0.0	3.0
16	620.4	615.6	625.2	620.8	628.8	617.2	623.6	612.4	0.0	3.0
17	465.6	620.4	476.0	629.2	488.0	614.4	477.6	606.0	0.0	5.0
18	357.8	540.4	405.9	575.4	407.3	573.5	358.6	538.8	0.0	2.0
19	405.9	574.6	353.8	661.7	355.5	663.1	407.9	574.3	0.0	2.0
20	354.1	662.0	414.6	710.1	416.8	710.1	355.8	661.7	0.0	2.0
21	414.6	709.8	517.6	728.9	519.3	727.5	413.8	708.4	0.0	2.0
22	517.4	728.3	519.3	728.3	551.8	693.0	550.1	691.9	0.0	2.0
23	564.1	677.9	573.1	666.2	572.0	665.0	563.0	677.1	0.0	2.0
24	572.8	666.7	573.4	665.6	474.0	581.9	472.8	583.3	0.0	2.0
25	474.2	581.9	419.9	551.9	419.4	553.9	472.3	582.7	0.0	2.0
26	420.2	552.5	370.6	519.4	369.5	521.1	419.6	553.9	0.0	2.0

WSPÓRCZYNNIKI ODBICIA DLA ŒCIAN

Nr	ściana 1	ściana 2	ściana 3	ściana 4	dach

1	1.0000	1.0000	1.0000	1.0000	1.0000
2	1.0000	1.0000	1.0000	1.0000	1.0000
3	1.0000	1.0000	1.0000	1.0000	1.0000
4	1.0000	1.0000	1.0000	1.0000	1.0000
5	1.0000	1.0000	1.0000	1.0000	1.0000
6	1.0000	1.0000	1.0000	1.0000	1.0000
7	1.0000	1.0000	1.0000	1.0000	1.0000
8	1.0000	1.0000	1.0000	1.0000	1.0000
9	1.0000	1.0000	1.0000	1.0000	1.0000
10	1.0000	1.0000	1.0000	1.0000	1.0000
11	1.0000	1.0000	1.0000	1.0000	1.0000
12	1.0000	1.0000	1.0000	1.0000	1.0000
13	1.0000	1.0000	1.0000	1.0000	1.0000
14	1.0000	1.0000	1.0000	1.0000	1.0000
15	1.0000	1.0000	1.0000	1.0000	1.0000
16	1.0000	1.0000	1.0000	1.0000	1.0000
17	1.0000	1.0000	1.0000	1.0000	1.0000
18	1.0000	1.0000	1.0000	1.0000	1.0000
19	1.0000	1.0000	1.0000	1.0000	1.0000
20	1.0000	1.0000	1.0000	1.0000	1.0000
21	1.0000	1.0000	1.0000	1.0000	1.0000
22	1.0000	1.0000	1.0000	1.0000	1.0000
23	1.0000	1.0000	1.0000	1.0000	1.0000
24	1.0000	1.0000	1.0000	1.0000	1.0000
25	1.0000	1.0000	1.0000	1.0000	1.0000
26	1.0000	1.0000	1.0000	1.0000	1.0000

=====

Punkty obserwacji

Nr	Symbol	X [m]	Y [m]	z [m]
1		431.6	814.1	4.0
2		641.9	590.2	4.0
3		572.0	530.3	4.0
4		488.4	474.4	4.0
5		421.9	487.2	4.0
